

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 December 2000 (14.12.2000)


PCT

(10) International Publication Number
WO 00/75854 A1

- (51) International Patent Classification⁷: G06F 19/00 (74) Agent: BOUCHARD, John, H.; Geo Quest, a division of Schlumberger, Suite 1700, 5599 San Felipe, Houston, TX 77056-2722 (US).
- (21) International Application Number: PCT/US00/15056
- (22) International Filing Date: 31 May 2000 (31.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/325,170 3 June 1999 (03.06.1999) US
- (71) Applicant: SCHLUMBERGER TECHNOLOGY CORPORATION [US/US]; 5599 San Felipe, Suite 1700, Houston, TX 77056-2722 (US).
- (72) Inventor: WALLIS, John, R.; 3722 Belle Grove, Sugar Land, TX 77479 (US).
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: AN IMPROVED SIMULATION METHOD AND APPARATUS



(57) Abstract: A Linear Solver method and apparatus, embodied in a Simulator, (70), and adapted for solving systems of non-linear partial differential equations and systems of linear equations representing physical characteristics of an oil and/or gas reservoir, (72), includes receiving a first signal representing physical characteristics of a reservoir, obtaining a residual vector, (Ro) from the first signal (representing errors associated with a system of nonlinear equations describing the reservoir), and a first matrix, (Ao), (78), (representing the sensitivity of the residual vector to changes in a system of nonlinear equations), recursively decomposing matrix (Ao), into a lower block triangular matrix, an upper block triangular matrix, and a diagonal matrix, and generating, (80), a second matrix (Mo) that is an approximation to matrix, (Ao). A solution to the systems of non-linear partial differential equations may then be found by using certain values that were used to produce the matrix, (Mo), and that solution, (86), does not require the direct computation of (Ao) z = b, (representing the system of linear equations) as required by conventional methods.

WO 00/75854 A1



Published:

— *With international search report.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

AN IMPROVED SIMULATION METHOD AND APPARATUS

5

BACKGROUND OF THE INVENTION

The subject matter of the present invention relates to a simulator software method and apparatus, embodied in an earth formation reservoir simulator, for simulating an earth formation reservoir containing liquids and/or gases by solving a system of linear equations that characterize physical aspects of an oil and/or gas field, the amount of time required by the reservoir simulator to solve the system of linear equations and to thereby simulate the earth formation reservoir being reduced relative to prior art simulation methods practiced by prior art simulators.

Oil and gas is produced from underground rock formations. These rocks are porous, just like a sponge, and they are filled with fluid, usually water. This porous characteristic of rocks is known as porosity. These rocks in addition to being porous have the ability to allow fluids to flow through the pores, a characteristic measured by a property called permeability. When oil (or gas) is trapped in such formations, it may be possible to extract it by drilling wells that tap into the formation. As long as the pressure in the well is lower than that in the rock formation, the fluids contained in the pores will flow into the well. These fluids may then flow naturally up the well to the surface, or the flow up the well may have to be assisted by pumps. The relative amounts of oil, gas and water that are produced at the surface will depend on the fraction of the rock pore space that is occupied by each type of fluid. Water is always present in the pores, but it will not flow unless its volume fraction exceeds a threshold value that varies from one type of rock to another. Similarly, oil and gas will only flow as long as their volume fractions exceed their own thresholds.

The characteristics of the rock (including porosity and permeability) in an oil reservoir vary greatly from one location to another. As a result, the relative amounts of oil, gas and water that can be produced will also vary from reservoir to reservoir. These variations make it difficult to simply predict the amount of fluids and gases a

reservoir will produce and the amount of resources it will require to produce from a particular reservoir. However, the parties interested in producing from a reservoir need to project the production of the reservoir with some accuracy in order to determine the feasibility of producing from that reservoir. Therefore, in order to accurately forecast production rates from all of the wells in a reservoir, it is necessary to build a detailed mathematical model of the reservoir's geology and geometry.

A large amount of research has been focused on the development of reservoir simulation tools. These tools include mathematical and computer models that describe and which are used to predict, the multiphase flow of oil and gas within a three dimensional underground formation (a "field"). Reservoir tools use empirically acquired data to describe a field. These data are combined with and manipulated by mathematical models whose output describes specified characteristics of the field at a future time and in terms of measurable quantities such as the production or injection rates of individual wells and groups of wells, the bottom hole or tubing head pressure at each well, and the distribution of pressure and fluid phases within the reservoir.

The mathematical model of a reservoir is typically done by dividing the reservoir volume into a large number of interconnected cells and estimating the average permeability, porosity and other rock properties for each cell. This process makes use of seismic data, well logs, and rock cores recovered when wells are drilled. Production from the reservoir can then be mathematically modeled by numerically solving a system of three or more nonlinear, partial differential equations describing fluid flow in the reservoir.

Computer analysis of production from an oil reservoir is usually divided into two phases, history matching and prediction. In the history matching phase, the past production behavior of the reservoir and its wells is repeatedly modeled, beginning with initial production and continuing up to the present time. The first computer run is based on a geological model as described above. After each run, the computer results are compared in detail with data gathered in the oil field during the entire

period of production. Geoscientists modify the geological model of the reservoir on the basis of the differences between computed and actual production performance and rerun the computer model. This process continues until the mathematical reservoir model behaves like the real oil reservoir.

5

Once a suitable history match has been obtained, production from the oil reservoir can be predicted far into the future (sometimes for as long as 50 years). Oil recovery can be maximized and production costs minimized by comparing many alternative operating plans, each requiring a new run of the computer model. After a field development plan is put into action, the reservoir model may be periodically rerun and further tuned to improve its ability to match newly gathered production data.

10

When sufficient data is obtained about the reservoir, characteristics of a reservoir can be mathematically modeled to predict production rates from wells in that reservoir. The gross characteristics of the field include the porosity and permeability of the reservoir rocks, the thickness of the geological zones, the location and characteristics of geological faults, relative permeability and capillary pressure functions and such characteristics of the reservoir fluids as density, viscosity and phase equilibrium relationships. From this data, a set of continuous partial differential equations (PDEs) are generated that describe the behavior of the field as a function of time and production parameters. These production parameters include the locations of wells, the characteristics of the well's completions, and the operating constraints applied to the wells. Operating constraints may include such as the production rate of a particular fluid phase, the bottom hole pressure, the tubing head pressure, or the combined flow rates of a group of wells. These constraints may be applied directly by data or by means of another simulator that models the flow of fluids in the surface equipment used to transport the fluids produced from or injected into the wells. However, because only the simplest system of PDEs can be solved using classic or closed-form techniques (e.g., a homogeneous field having circular boundaries), a model's PDEs are converted into a set of non-linear approximations which are then solved numerically. One approximation technique is the finite difference method. In the finite difference method, reservoir PDEs are converted into a series of difference quotients which

15

20

25

30

divide a reservoir into a collection of discrete three dimensional cells, which are then solved for at discrete times to determine (or predict) the value of reservoir characteristics such as pressure, permeability, fluid fractions, and at a later time.

- 5 Within the computerized reservoir simulator, reservoir performance is modeled in discrete increments of time. Each so-called timestep advances the solution from a previous point in time, where all variables are known, to a future point in time, where all variables are unknown. This process is repeated until the entire time period of interest has been modeled. Within each timestep it is necessary to solve a
- 10 huge system of nonlinear equations that models fluid flow from cell to cell and through the wells. (With current technology it is possible to include several million cells in the reservoir model.) Solutions to the system of nonlinear equations are obtained by Newton iteration. In each such iteration the system of nonlinear equations is approximated by a system of linear equations, which must be solved by
- 15 yet another iterative procedure.

- A general outline of the operation of a reservoir simulator follows (refer to figure 8a). Reservoir data and rock core data are used to describe a computational grid and the properties of the reservoir rocks. This is combined with data on the
- 20 physical properties of the fluids contained in the reservoir and used to compute the initial distributions of pressure and fluid saturations (volume fractions) as well as the composition of each fluid phase. Time varying data, such as the locations and characteristics of wells, production and injection flow rate controls, and simulator control information, is read from a data base. Using the current pressure, saturation,
- 25 and fluid compositions for each grid cell, the partial differential equations describing mass balances are approximated by finite differences resulting in two or more nonlinear algebraic equations for each cell. In addition, these nonlinear equations are linearized by means of Newton's method. The resulting system of linear equations is solved iteratively using methods described in this specification. After
- 30 the linear equations have been solved, a test is performed to determine whether all of the nonlinear terms in the finite difference equations have converged. If not, the simulator returns to a previous step wherein the partial differential equations describing mass balances are approximated by finite differences. However, if the

nonlinear terms have converged, the simulator updates values to complete the current timestep. Then, the simulator tests to determine whether the desired ending time in the simulation has been reached. If not, the simulator returns to a previous step to read new time varying data and begins the next timestep. However, if the endpoint of the simulation has been reached, then, the simulator completes output operations and the run is finished.

As reservoir simulations grow in complexity (e.g., number of parameters) and size (e.g., number of cells), solving the resulting system of linear equations, represented by the matrix equation $A \cdot x = b$, requires an increasingly large effort. For example, the work involving the iterative solution increases with the square of the number of parameters per cell. In many reservoir models, the time required to solve systems of linear equations (step 56 in figure 8a) can be a limiting factor on the simulation's usefulness.

In connection with reservoir modeling, well logging operations are performed in the formation thereby producing well log data, and seismic operations are performed on the formation thereby producing seismic data. The seismic data is reduced thereby producing reduced seismic data. The well log data and the reduced seismic data are introduced, as input data, to a computer workstation which stores a gridding software and a simulator software. A gridding software, hereinafter known as 'the Flogrid software' or the 'Flogrid gridding software', is disclosed in prior pending U.S. patent application serial number 09/034,701, filed in the U.S. on March 4, 1998, which is based on a Great Britain patent application number 9727288.4 filed December 24, 1997, the disclosure of which is incorporated by reference into this specification. The 'Flogrid' gridding software includes another gridding software known as 'Petragrid'. The 'Petragrid' gridding software is disclosed in prior pending U.S. patent application serial number 08/873,234 filed June 11, 1997, the disclosure of which is also incorporated by reference into this specification. The gridding software will respond to the reduced seismic data and the well log data by gridding the earth formation which was subjected to the well log operation and the seismic operation. The type of grids imposed on the earth formation include structured (approximately rectangular) grids and unstructured (tetrahedral) grids. A property,

such as permeability or water saturation, is assigned to each cell or grid block of the grid. As a result, a set of output data is generated by the gridding software, the set of output data including the plurality of cells/grid blocks of the grid and the respective plurality of properties associated with each of the cells of the grid.

5

The set of output data from the gridding software are introduced, as input data, to a reservoir simulator software. The reservoir simulator software will respond to the set of output data from the gridding software by generating a plurality of simulation results which are associated, respectively, with the plurality of cells/grid blocks of the grid received from the gridding software. The plurality of simulation results and the plurality of cells/grid blocks associated therewith, generated by the reservoir simulator software, will be displayed on a 3D viewer of the workstation for observation by a workstation operator. Alternatively, the plurality of simulation results and the plurality of cells/grid blocks associated therewith can be recorded for observation by a workstation recorder.

15

The reservoir simulator software can model an oilfield reservoir. For example, in the Society of Petroleum Engineers (SPE) publication number 28545, concerning a transient tool for multiphase pipeline and well simulation, dated 1994, the authors have solved for pressure losses along a single pipeline using a technique related to conservation of material and conservation of pressure. A similar technique has been applied to a network of pipelines or flowlines in the Society of Petroleum Engineers (SPE) publication number 29125, authored by Litvak and Darlow. In this publication, the authors (Litvak and Darlow) have taken a network model (i.e., a network of pipelines) in which the pressure losses along the network branches can either be calculated from tables or from an analytical model, and the analytical model solves for three (3) conservations and pressures. In addition, in an article by the "Society of Petroleum Engineers" (SPE) 12259, each well being modeled in that article was characterized by three (3) variables: pressure, water fraction, and gas fraction.

25
30

As noted earlier, in many reservoir models, the time required to solve systems of linear equations (step 56 in figure 8a) can be a limiting factor on the simulation's

usefulness. Accordingly, it would be beneficial to have a method that can be used to efficiently solve large systems of linear equations. It is the solution of this system of linear equations that is the subject of the invention of this specification.

- 5 Accordingly, a new and improved reservoir simulator software is needed wherein the amount of time required to execute the new and improved reservoir simulator software is much less than the amount of time required to execute the reservoir simulator software of the prior art.

10

SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the present invention to provide an improved method of performing computer simulations.

- 15 It is a primary aspect of this invention to provide a simulation program that includes a "Linear Solver" method and apparatus which operates with reduced processing time relative to prior art simulators.

- 20 It is a further aspect of this invention to provide a simulation program that includes a "Linear Solver" method and apparatus which practices a method for solving systems of differential equations having substantially fewer steps than conventional methods of solving differential equations.

- 25 It is a further aspect of this invention to provide a simulation program which includes a "Linear Solver" method and apparatus that generates a set of simulation results prior to completely solving a system of differential equations.

- 30 In accordance with the primary object and other aspects of the present invention, an improved "Linear Solver" method and apparatus is disclosed for simulating conditions and characteristics that are mathematically modeled using linear and non-linear systems of differential equations. These systems of differential equations are very large and complex and require substantial processing time to solve. The processing time required to execute a simulation program can have an effect on the

accuracy of the simulation results. The present invention provides a faster method to solve differential equation systems by generating a smaller approximated matrix that is an approximation of the system of equations. This smaller approximated matrix is smaller than another matrix that represents the original system of equations. From the smaller approximated matrix, information that is usually determined from the solved equations is obtained prior to the step of solving the differential equation system. The reduced size of the smaller approximated matrix, coupled with the fact that some of the final information is obtained prior to completely solving the system of differential equations, results in a faster simulation method.

Consequently, the 'Linear Solver' of the present invention provides a method for solving a system of linear equations representing physical characteristics of an oil and/or gas reservoir. This method includes receiving a first signal representing physical characteristics of the reservoir, obtaining a residual vector \bar{r}_0 (representing errors associated with a system of nonlinear equations describing the reservoir) and a first matrix A_0 (representing the sensitivity of the residual vector \bar{r}_0 to changes in the system of nonlinear equations) from the received first signal; recursively decomposing matrix A_0 into a lower block triangular matrix, an upper block triangular matrix, and a diagonal matrix; and generating a second matrix M_0 that is an approximation to matrix A_0 . The invention further provides generating an approximate solution for the system of linear equations (in the form of a signal) without directly computing the matrix multiplication $A_0 \bar{x} = \bar{b}$ required of conventional techniques.

At each time step of the simulation, it is necessary to solve a system of linear equations represented by $A_0 x = r_0$. A_0 is a matrix obtained from the data input into the simulation program. A_0 is a sparse matrix in that there are few non-zero elements in the matrix. Because of the size of the matrix, it would be very costly to solve the system of differential equations associated with this matrix A_0 directly.

Therefore, A_0 is decomposed into smaller matrix components that will be easier to factor, including an upper matrix component, a lower matrix component and diagonal matrix components.

- 5 An approximate matrix M_0 is generated from the matrix components. This matrix M_0 can be factored. Once the factorization process is complete, this matrix M_0 can be solved to get a result similar to the result obtained from solving the original matrix A_0 . However, solving the M_0 matrix requires much less time than the original matrix A_0 would require. This process is possible because data normally
- 10 determined from solving the original matrix A_0 is obtained from information determined during the factorization of matrix M_0 . Therefore, the process time required to solve the matrix M_0 is much less because some of the information obtained from solving the original matrix A_0 has already been determined during the factorization of matrix M_0 .

15

- The inventive concept may be embodied in a computer program stored in any media that is readable and executable by a computer system. Illustrative media include magnetic and optical storage devices. Illustrative programming languages include Fortran and C. Illustrative computer systems include personal computers,
- 20 engineering workstations, minicomputers, mainframe computers, and specially designed state machines.

25

Further scope of applicability of the present invention will become apparent from the detailed description presented hereinafter. It should be understood, however, that the detailed description and the specific examples, while representing a preferred embodiment of the present invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become obvious to one skilled in the art from a reading of the following detailed description.

30

BRIEF DESCRIPTION OF THE DRAWINGS

A full understanding of the present invention will be obtained from the detailed description of the preferred embodiment presented hereinbelow, and the accompanying drawings, which are given by way of illustration only and are not
5 intended to be limitative of the present invention, and wherein:

figure 1 illustrates a seismic operation for producing a reduced seismic data output record, the seismic operation of figure 1 including a data reduction operation;

10

figure 2 illustrates a wellbore operation for producing a well log output record;

figure 3 illustrates a computer system for performing the data reduction operation of figure 1;

15

figures 4 and 5 illustrate a workstation adapted for storing a "Flogrid" software and an "Eclipse" simulator software;

20

figures 6 and 6a illustrate a more detailed construction of the "Flogrid" software of figure 5 which is adapted for generating output data for use by the "Eclipse" simulator software, the Eclipse simulator software including a "Linear Solver method and apparatus" in accordance with the present invention;

25

figure 7 illustrates an example of a typical output display generated by the "Eclipse" simulator software of figure 6 which is displayed on the 3D viewer of figure 6;

30

figure 8a illustrates a prior art approach or method of performing reservoir simulation which has been practiced by prior art reservoir simulators;

figure 8b illustrates the Eclipse simulator software of figure 5 including the Linear Solver of the present invention;

figures 9 through 13 illustrate the 'Linear Solver' method and apparatus in accordance with the present invention which is embodied in the 'Eclipse simulator software' of figures 5 and 6, and wherein:

- 5 figure 9 illustrates the approach or method of performing reservoir simulation practiced by the 'Eclipse' simulator software of present invention;

figure 10 outlines a technique or method for solving a system of linear equations;

- 10 figure 11 illustrates a matrix decomposition technique or method practiced by the 'Eclipse' simulator software of the present invention;

figure 12 illustrates a factorization technique practiced by the 'Eclipse' simulator software in the present invention; and

15

figure 13 illustrates a method for producing an approximate solution to an original system of linear equations in accordance with an inventive concept of the present invention.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

25

The 'Eclipse' simulator software of the present invention receives output data from the 'Flogrid' simulation gridding software and, responsive thereto, the 'Eclipse' simulator software generates a set of simulation results which are displayed on a 3D viewer. The 'Eclipse' simulator software includes the 'Linear Solver' method and apparatus in accordance with the present invention. The 'Linear Solver' apparatus of the present invention includes a special apparatus which allows the simulation processing time of the 'Eclipse' simulator to be substantially less than the processing time associated with the prior art reservoir simulators.

30

This specification is divided into two parts: (1) a Background discussion which provides background information relating to the performance of a seismic operation and a well logging operation adapted for generating seismic and well logging data,

the seismic and well logging data being provided as input data to a workstation that stores a 'Flogrid' simulation gridding software and an 'Eclipse' simulator software, and (2) a more detailed description of the 'Eclipse' simulator software, the 'Eclipse' simulator software including a 'Linear Solver' method and apparatus in accordance with the present invention which causes or allows the simulation processing time of the Eclipse simulator to be substantially less than the simulation processing time associated with other prior art simulators.

Background Discussion

10

Referring to figure 1, a method and apparatus for performing a seismic operation is illustrated. During a seismic operation, a source of acoustic energy or sound vibrations 10, such as an explosive energy source 10, produces a plurality of sound vibrations. In figure 1, one such sound vibration 12 reflects off a plurality of horizons 14 in an earth formation 16. The sound vibration(s) 12 is (are) received in a plurality of geophone-receivers 18 situated on the earth's surface, and the geophones 18 produce electrical output signals, referred to as "data received" 20 in figure 1, in response to the received sound vibration(s) 12 representative of different parameters (such as amplitude and/or frequency) of the sound vibration(s) 12. The "data received" 20 is provided as "input data" to a computer 22a of a recording truck 22, and, responsive to the "input data", the recording truck computer 22a generates a "seismic data output record" 24. Later in the processing of the seismic data output record 24, such seismic data undergoes "data reduction" 30 in a mainframe computer, and a "reduced seismic data output record" 24a is generated from that data reduction operation 30.

25

Referring to figure 2, a well logging operation is illustrated. During the well logging operation, a well logging tool 34 is lowered into the earth formation 16 of figure 1 which is penetrated by a borehole 36. In response to the well logging operation, well log data 38 is generated from the well logging tool 34, the well log data 38 being provided as "input data" to a computer 40a of a well logging truck 40. Responsive to the well log data 38, the well logging truck computer 40a produces a "well log output record" 42.

30

Referring to figure 3, the seismic data output record 24 of figure 1 is provided as 'input data' to a mainframe computer 30 where the data reduction operation 30 of figure 1 is performed. A mainframe processor 30a will execute a data reduction software 30b stored in a mainframe storage 30b. When the execution of the data reduction software 30b is complete, the reduced seismic data output record 24a of figures 1 and 3 is generated.

Referring to figures 4 and 5, a workstation 44 is illustrated in figure 4. A storage medium 46, such as a CD-Rom 46, stores software, and that software can be loaded into the workstation 44 for storage in the memory of the workstation. In figure 5, the workstation 44 includes a workstation memory 44a, the software stored on the storage medium (CD-Rom) 46 being loaded into the workstation 44 and stored in the workstation memory 44a. A workstation processor 44d will execute the software stored in the workstation memory 44a in response to certain input data provided to the workstation processor 44d, and then the processor 44d will display or record the results of that processing on the workstation 'recorder or display or 3D viewer' 44e. The input data, that is provided to the workstation 44 in figure 5, includes the well log output record 42 and the reduced seismic data output record 24a. The 'well log output record' 42 represents the well log data generated during the well logging operation in an earth formation of figure 2, and the 'reduced seismic data output record' 24a represents data-reduced seismic data generated by the mainframe computer 30 in figure 3 in response to the seismic operation illustrated in figure 1. In figure 5, the software stored on the storage medium (CD-Rom) 46 in figure 5 includes a 'Flogrid' software 46a and an 'Eclipse' simulator software 46b. When the storage medium (CD-Rom) 46 is inserted into the workstation 44 of figure 5, the 'Flogrid' software 46a and the 'Eclipse' simulator software 46b, stored on the CD-Rom 46, are both loaded into the workstation 44 and stored in the workstation memory 44a. The 'Flogrid' software 46a is fully described and set forth in pending U.S. patent application serial number 09/034,701, filed in the U.S. on March 4, 1998, which is based on prior pending Great Britain patent application number 9727288.4 filed December 24, 1997, the disclosure of which is incorporated by reference into this specification. When the workstation processor 44d executes the

Flogrid software 46a and the Eclipse simulator software 46b, the 'Eclipse' simulator software 46b responds to a set of more accurate grid cell property information associated with a respective set of grid blocks of a structured simulation grid generated by the 'Flogrid' software 46a by further generating a set of more accurate simulation results which are associated, respectively, with the set of grid blocks of the simulation grid. Those simulation results are displayed on the 3D viewer 44e of figure 5 and can be recorded on a recorder 44e.

Referring to figures 6 and 6a, in figure 6, the Flogrid software 46a and the Eclipse simulator software 46b are illustrated as being stored in the workstation memory 44a of figure 5. In addition, the 'simulation results' 48, which are output from the Eclipse simulator software 46b, are illustrated as being received by and displayed on the 3D viewer 44e. The Flogrid software 46a includes a reservoir data store, a reservoir framework, a structured gridder, an unstructured gridder, and an upscaler, all of which are fully discussed in the above referenced prior pending U.S. patent application serial number 09/034,701, filed in the U.S. on March 4, 1998, the disclosure of which has already been incorporated by reference into this specification. In figure 6, a set of 'simulation grids and properties associated with the grids' 47, generated by the Upscaler and the 'Petragrid' unstructured gridder, are received by the Eclipse simulator software 46b. In response, the Eclipse simulator software 46b generates a 'set of simulation results associated, respectively, with a set of grid blocks of the simulation grids' 48, and the simulation results and the associated grid blocks 48 are displayed on the 3D viewer 44e.

In figure 6a, the Flogrid software 46a generates a set of output data 47 comprising a plurality of grid cells and certain properties associated with those grid cells. That output data 47 is provided as input data to the Eclipse simulator software 46b. Some other programs 49 provide other input data to the Eclipse simulator software 46b. In response to the output data 47 (comprised of a gridded earth formation including a plurality of grid cells and certain properties associated with each of the grid cells), as well as the other output data from the other programs 49, the Eclipse simulator software 46b generates a set of 'simulation results' 48, the simulation results 48 including the plurality of grid cells and a plurality of simulation results associated,

respectively, with the plurality of grid cells. The aforementioned plurality of grid cells and the plurality of simulation results associated, respectively, with the plurality of grid cells are displayed on the 3D Viewer 44e of figure 6 and 6a.

5 Referring to figure 7, an example of the simulation results 48 (i.e., the "plurality of grid cells and the plurality of simulation results associated, respectively, with the plurality of grid cells" 48) which are displayed on the 3D viewer 44e of figures 5 and 6 and 6a, is illustrated in figure 7.

10 Detailed Description of the Eclipse simulator software 46b of figures 5 and 6 including the "Linear Solver" method and apparatus in accordance with the present invention

Referring to figure 8a, a general outline of the operation of a prior art reservoir
15 simulator is discussed below with reference to figure 8a. In figure 8a, reservoir data 42 and 24a of figure 5 and rock core data are used to describe a computational grid and the properties of the reservoir rocks. This data is combined with data relating to the physical properties of the fluids contained in the reservoir, the combined data being used to compute the initial distributions of pressure and fluid saturations
20 (volume fractions) as well as the composition of each fluid phase, block 50 in figure 8a. Time varying data, such as the locations and characteristics of wells, production and injection flow rate controls, and simulator control information is read from a data base, block 52. Using the current pressure, saturation, and fluid compositions for each grid cell, the partial differential equations describing mass balances are
25 approximated by finite differences in block 54 which results in two or more nonlinear algebraic equations for each grid cell. Also, in block 54, these nonlinear equations are linearized by means of Newton's method. In block 56, the resulting system of linear equations is solved iteratively, using methods described in this specification. After the linear equations have been solved, there is a test in block 58
30 to determine whether all of the nonlinear terms in the finite difference equations have converged. If not, the simulator returns to block 54. If the nonlinear terms in the finite difference equations have converged, the simulator moves to block 60 and updates values to complete the current timestep. In block 62, the simulator tests to determine whether the desired ending time (i.e., the stop time) in the simulation has

been reached. If not, the simulator advances time to the next level, block 64, and then it returns to block 52 to read new time varying data and to begin the next timestep. If the endpoint of the simulation has been reached, then, the simulator completes output operations and the run is finished, block 66.

5

Referring to figure 8b, as noted earlier, the Eclipse simulator software 46b of figures 5 and 6 includes the "Linear Solver" 70 in accordance with the present invention. The Linear Solver 70 substantially reduces the simulation processing time which is normally associated with prior art reservoir simulators.

10

As noted earlier with reference to figure 8a, blocks 54 and 56, nonlinear partial differential equations are linearized (block 54 of figure 8a) and the resulting system of linear equations is solved iteratively, using methods discussed in this specification (block 56 of figure 8a). If the nonlinear terms are not converged (block 58 in figure 8a), the following discussion with reference to figures 9 through 13 will discuss those methods for solving a system of non-linear partial differential equations.

15

Referring to figure 9, a description of the Linear Solver 70 of the present invention of figure 8b will be discussed below in the context of a novel method for solving a system of nonlinear partial differential equations that represent an oil or gas reservoir, that novel method being illustrated in figure 9.

20

The basic distinction between this invention and the conventional simulation methods is the way step 56 of figure 8a is performed (i.e., 'iteratively solve the linear equations'). Systems of differential equations are very large and to solve them directly requires solving the equation $A_0 \bar{x} = \bar{b}$ for each time step of the simulation process. The conventional method would require substantial time and effort. To reduce the amount of processing time, the conventional simulation methods would require a reduction the amount of input data, which prevents a more accurate simulation. However, the simulation method (and apparatus) of the present invention performed by the Linerar Solver 70 performs steps that enable one to

25

30

directly avoid the equation $A_0 \bar{x} = \bar{b}$ by solving an approximate system of equations in less time and without sacrificing accuracy in the results.

In figure 9, the Linear Solver 70 simulation method of present invention:

- 5 (1) converts the system of non-linear equations into a system of linear equations, block 76 of figure 9; (2) solves the system of linear equations; and then (3) solves the system of non-linear equations using the solved system of linear equations obtained during step (2).
- 10 The method practiced by the Linear Solver 70 of figure 8b of the present invention, for solving the system of linear equations from step (2) above, involves four basic steps that distinguishes the simulation method of the present invention from the conventional simulation methods. These four basic steps are set forth below with reference to figure 9 as follows:
- 15 (1) Obtain a matrix A_0 of the system of linear differential equations, block 78 in figure 9;
- (2) Decompose this matrix A_0 into components [i.e., an upper block component, a lower block component, and a diagonal component], to facilitate factorization of
20 the matrix A_0 , until a new factorable matrix M_0 is obtained, block 80 in figure 9;
- (3) Compute a factorization of this new factorable matrix M_0 , block 82 in figure 9, to produce a system of linear equations that approximates the original matrix A_0 ; and
- 25 (4) Solve the system of linear equations from step (3) which are represented by matrix M_0 , block 84 of figure 9.

This solution to matrix M_0 gives an approximate but accurate solution to the original matrix A_0 . This solution to matrix M_0 is then used to solve the system of
30 non-linear equations, block 86 in figure 9. The advantage of solving the

matrix M_0 is that this matrix M_0 requires much less time to solve. In addition, the accuracy of the matrix M_0 is not a compromise because much of the 'information' that is usually determined from calculating the matrix A_0 is calculated during the factorization step of matrix M_0 (block 82 of fig. 9). Because this 'information' is already calculated from the factorization step of matrix M_0 , block 82, there is no need to calculate this 'information' when solving matrix M_0 , block 84. Therefore it takes less time to solve this matrix M_0 because there are fewer components to calculate.

- 10 In figure 9, generate a system of approximate linear equations from the original system of nonlinear equations, block 76 of figure 9, and generate a matrix A_0 from these linear equations, block 78. The matrix A_0 , generated from the linear equations in block 78 of figure 9, is sparse in that it contains few non-zero elements. The small number of non-zero elements in this matrix A_0 and the fact that this
- 15 matrix A_0 is very large and complex make it very difficult to solve the resulting system of equations directly. In order to solve this matrix A_0 , the matrix A_0 is first decomposed into components (upper block, lower block and a diagonal), block 80 of figure 9. This decomposition divides the matrix A_0 into a plurality of smaller matrix blocks. Each of the plurality of smaller matrix blocks of the matrix A_0 is
- 20 then recursively decomposed (the upper block from bottom to top and the lower block from top to bottom)) until a resulting matrix M_0 is generated which can be efficiently factored exactly (block 80). This decomposition of the matrix A_0 results in a new matrix M_0 that is an approximation of the original matrix A_0 . The next step, block 82 of figure 9, involves the computation of a factorization of the matrix
- 25 M_0 , the computation of the factorization of the matrix M_0 generating a system of equations which is an approximation of the original set of linear equations and which can be more efficiently solved. This factorization step (computing the factorization of matrix M_0 , block 82 of figure 9) generates the following equation:

$$M_0 = (L_0 M_1^{-1} + 1)(M_1 + U_0)$$

The solution of the above equation " $M_0 = (L_0 M_1^{-1} + 1)(M_1 + U_0)$ " for

5 matrix M_0 , block 84 of figure 9, can be used to determine the solution to the original system of non-linear equations, block 86 of figure 9.

As indicated in block 82 of figure 9 (and the above step 3), one widely used technique to solve systems of linear equations is 'nested factorization' which is
 10 defined to be an iterative technique for determining an approximate matrix corresponding to the system's coefficient matrix. A system of linear equations representing reservoir characteristics may be solved by exploiting certain, and heretofore unrecognized, characteristics of the nested factorization method. The following embodiment of this inventive concept, relating to oil and gas reservoir
 15 modeling, is illustrative only and is not to be considered limiting in any respect.

Referring to figures 10 through 13, these figures will discuss, in detail, some of the individual steps of figure 9 which are practiced by the Linear Solver 70 of the present invention.

20

In figure 10, a system of linear equations (represented by the matrix equation $A_0 \bar{x} = \bar{r}_0$), which have been derived from partial differential equations (PDEs) via finite difference quotients, can be characterized, for each iteration, as a seven step process. In figure 10, block 88, an initial matrix A_0 and an initial residual vector
 25 \bar{r}_0 are obtained. Initial residual vector \bar{r}_0 is the vector of current errors (residuals) for the system of nonlinear equations. Matrix A_0 is a sparse Jacobian matrix that describes the sensitivity of the residuals to changes in \bar{x} for the system of nonlinear equations. In block 90 of figure 10, matrix A_0 is decomposed into smaller and smaller matrices until a matrix is found which is efficiently factored exactly. A
 30 matrix can be efficiently factored exactly when it has a bandwidth of less than or

equal to approximately 7. Starting with the largest decomposed matrix of A_0 that can be efficiently factored exactly (found in block 90 of figure 10), an approximate factorization for matrix A_0 is found such that $A_0 = M_0 = LU$ where L is a block lower triangular and U is a block upper triangular matrix, block 92 of figure 10.

5 Using the LU factorization of matrix A_0 (i.e., matrix M_0), the value of $A_0 \bar{s}$ is computed where \bar{s} is a computed approximation for the original linear system at the current time step, block 94 of figure 10. A predicted value of $A_0 \bar{s}$ is then computed for the next time step, block 96 of figure 10, which is then checked for convergence. If the predicted value $A_0 \bar{s}$ converges (the 'yes' prong of block 98 in
10 figure 10), the current time step has been completed, block 100 of figure 10. If the predicted value of $A_0 \bar{s}$ does not converge (the 'no' prong of block 98), blocks 94 and 96 of figure 10 are repeated. Blocks 88 through 100 of figure 10 are repeated for each time step in the simulation.

15 In figure 11, a modified nested factorization technique to decompose matrix A_0 (i.e., block 92 of figure 10) is illustrated in figure 11. After initializing loop variable 'i' to zero, block 102 of figure 11, a test is made to determine if the matrix denoted by A_i can be efficiently factored exactly. If matrix A_i cannot be efficiently factored exactly (the 'no' prong of block 104 of figure 11), matrix A_i is partitioned (i.e.,
20 decomposed) such that $A_i = L_i + A_{i+1} + U_i$ where L_i is a lower triangular matrix, U_i is an upper triangular matrix, and A_{i+1} is a block diagonal matrix, block 106 of figure 11. Next, loop control variable 'i' is incremented (block 108 in figure 11) and processing continues at block 104 of figure 11. If matrix A_i can be efficiently factored exactly (the 'yes' prong of block 104 of figure 11), control
25 variable 'n' is assigned the current value of loop control variable 'i' (block 110 in figure 11). For computational efficiency, matrix A_n is preferably the largest (i.e., first found) decomposition of matrix A_0 that can be efficiently factored exactly.

In figure 12, a technique for generating an approximate factorization of matrix A_0 (block 92 in figure 10) is shown in figure 12. Matrix M_n is initialized to $A_n - D$ where matrix D is a diagonal matrix defined by:

$$5 \quad OP\left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1}\right) \text{ or } OP\left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1}\right), \text{ and}$$

OP represents either a column-sum operator or a row-sum operator (block 112 of figure 12). The column-sum of matrix X is a diagonal matrix formed by summing the elements of matrix X in columns. The row-sum of matrix X is a diagonal matrix
 10 formed by summing the elements of matrix X in rows. Next, loop variable 'i' is initialized to 'n-1' (block 116 of figure 12) and a test is made to determine if the factorization loop is complete. If variable 'i' does not equal zero (the 'no' prong of block 118 of figure 12), the next M_i matrix is computed in accordance with the following:

$$15 \quad M_i = (L_i + M_{i+1})(I + M_{i+1}^{-1} U_i),$$

where I represent the identity matrix (block 120 of figure 12). Loop control variable 'i' is then decremented (block 122), and processing continues at block 118. If
 20 variable 'i' equals zero (the 'yes' prong of block 118), matrix M_0 (the factored approximation to A_0) is computed in accordance with:

$$M_0 = (L_0 M_1^{-1} + I)(M_1 + U_0), \text{ block 124 of figure 12.}$$

25 In figure 13, during each iteration (step 94 through 100 of figure 10), an approximate solution \bar{x}' to the original system of linear equations ($A_0 \bar{x} = \bar{r}_0$) is generated in accordance with figure 13. First, an initial solution \bar{S}_0 is defined, e.g., $\bar{S}_0 = 0$ (block 126 of figure 13). Next, loop variable 'i' is initialized to 1 (block 128 of figure 13) and a test is made to determine if the current solution has converged. If

the current solution (e.g., that solution associated with the current time step) has not converged (the 'no' prong of block 130), the equation $M_0 \bar{S}_i = \bar{r}_{i-1}$ is solved for \bar{S}_i (block 132 of figure 13). One benefit of the methods illustrated in figures 11 and 12 is that the following interim results are obtained at no additional computational cost:

$$\bar{y} = (L_0 M_1^{-1} + I)^{-1} \bar{r}$$

$$\bar{q} = (M_1 + U_0)^{-1} \bar{y}; \text{ and}$$

$$\bar{z}_k = M_{k+1}^{-1} U_k \bar{q} \quad (\text{for } k=1, \dots, n-1)$$

These interim results can be used to compute a value for $A \bar{S}_i$, that is,

$A_0(M_0^{-1} \bar{r}_{i-1})$, in accordance with the following (block 134 of figure 13):

$$A_0(M_0^{-1} \bar{r}_{i-1}) = \bar{y} + D \bar{q} + L_0 \bar{q} - \sum_{k=1}^{n-1} L_k \bar{z}_k$$

The method of computing $A \bar{S}_i$ outlined above and in figure 13 uses only $(n + 1)$ diagonal vector multiplies, compared with the $(2n + m)$ diagonal vector multiplies required by prior matrix multiplication techniques [where 'n' equals the value determined at block 110 of figure 11, and 'm' equals the number of diagonals (e.g., the bandwidth) of A_n]. The computational savings provided by the inventive method over the prior technique in two, three, and four dimensional (i.e., 2-D, 3-D, and 4-D respectively) oil and gas reservoir simulations can be described in percentage terms as shown in Table 1 below:

Table 1: Computational Savings of Inventive Concept

	m	n	%-Savings
2-D Simulation	3	1	40
3-D Simulation	3	2	42.9
4-D Simulation	3	3	44.4

5 $\% \text{-Savings} = \frac{n+1}{2n+m} \times 100$

In figure 13, block 136, a value for vector \vec{r}_i may be calculated using any suitable acceleration method. Illustrative stationary acceleration methods include the Jacobi, Gauss-Seidel, successive overrelaxation (SOR), and symmetric successive overrelaxation (SSOR) methods. Illustrative nonstationary acceleration methods include the generalized minimal residual (GMRES), biconjugate gradient (BiCG), biconjugate gradient stabilized (Bi-CGSTAB), quasi-minimal residual (QMR), conjugate gradient squared (CGS), Chebyshev, and conjugate gradient (CG) techniques.

15 If the value of \vec{r}_i generated in block 136 of figure 13 converges (the 'yes' prong of block 130 is active), the approximate solution \vec{x}' associated with the current time step is computed in block 138 in figure 13 (i.e., $A_0 \vec{x}' = \vec{r}_i$ is solved for \vec{x}'). Convergence may be defined in any suitable manner and, in one embodiment, is said to occur when the ratio between the magnitude of \vec{r}_i and \vec{r}_{i+1} is less than 0.1%. Mathematically, this may be expressed in the following manner:

20

$$\frac{\|\vec{r}_{i+1}\|}{\|\vec{r}_i\|} \leq 0.001, \text{ where } \|\vec{a}\| \text{ represents the Euclidean norm of vector } \vec{a}.$$

- Method steps of figures 10 through 13 may be performed by a computer processor executing instructions organized into program modules. Storage devices suitable for tangibly embodying computer program instructions include all forms of non-volatile memory including, but not limited to: magnetic disks (fixed and floppy); other magnetic media such as tape; optical media such as CD-ROM disks; and semiconductor memory devices such as EPROM and flash devices.
- 10 The methods of this invention provide significant advantages over the current art. The invention has been described in connection with its preferred embodiments. However, it is not limited thereto. Changes, variations and modifications to the basic design may be made without departing from the inventive concepts in this invention. In addition, these changes, variations and modifications would be
- 15 obvious to those skilled in the art having the benefit of the foregoing teachings. All such changes, variations and modifications are intended to be within the scope of this invention, which is limited only by the following claims.

WE CLAIM:

1. A simulation apparatus responsive to input data adapted for solving a system of nonlinear equations that represent a particular entity, said simulation apparatus generating a set of simulation results when said system of nonlinear equations are solved, said set of simulation results including one or more parameters which characterize said particular entity, comprising:
 - 10 first means for converting said system of nonlinear equations into a system of linear equations;
 - second means for solving said system of linear equations thereby producing a set of results; and
 - 15 third means for solving said system of nonlinear equations by using said set of results produced by said second means.
2. The simulation apparatus of claim 1, wherein said input data includes reservoir data and said particular entity includes an oil or gas reservoir.
3. The simulation apparatus of claim 1, wherein said second means for solving said system of linear equations comprises:
 - 25 means for obtaining a matrix A_0 from the system of linear equations;
 - means for decomposing the matrix A_0 until a factorable matrix M_0 is obtained;

first computing means for computing an approximate factorization of the matrix M_0 to produce a particular system of linear equations, which are represented by said matrix M_0 , that approximates said matrix A_0 ; and

5 second computing means for computing a solution to said particular system of linear equations using said matrix M_0 .

4. The simulation apparatus of claim 3, wherein said third means solves said system of nonlinear equations by using said solution, computed by
10 said second computing means, to said particular system of linear equations which use said matrix M_0 .

5. In a workstation apparatus adapted to receive reservoir data including a simulator adapted for receiving said reservoir data and for generating a
15 set of simulation results which include one or more parameters representative of an oil or gas reservoir and a recorder or display apparatus adapted for recording or displaying said set of simulation results, said simulator comprising:

20 first means for converting said system of nonlinear equations into a system of linear equations;

second means for solving said system of linear equations thereby producing a set of results; and

25 third means for solving said system of nonlinear equations by using said set of results produced by said second means.

6. The simulator of claim 5, wherein said second means for solving said
30 system of linear equations comprises:

means for obtaining a matrix A_0 from the system of linear equations;

means for decomposing the matrix A_0 until a factorable matrix M_0 is obtained;

5

first computing means for computing an approximate factorization of the matrix M_0 to produce a particular system of linear equations, which are represented by said matrix M_0 , that approximates said matrix A_0 ; and

10 second computing means for computing a solution to said particular system of linear equations using said matrix M_0 .

7. The simulator of claim 6, wherein said third means solves said system of nonlinear equations by using said solution, computed by said second
15 computing means, to said particular system of linear equations which use said matrix M_0 .

8. In a simulator, a method for solving a system of linear equations representing reservoir conditions, comprising the steps of:

20

(1) receiving a first signal representing physical characteristics of a reservoir;

25

(2) obtaining, from the received signal, a residual vector \vec{r}_0 representing errors associated with a system of nonlinear equations describing the reservoir;

30

(3) obtaining, from the received signal, a first matrix A_0 representing sensitivity of the residual vector \vec{r}_0 to changes in the system of nonlinear equations describing the reservoir;

(4) decomposing matrix A_0 in accordance with the following steps:

- (a) letting $i = 0$,
- (b) if matrix A_i can be efficiently factored exactly, letting $n=i$,
 5 else,
 (i) letting $A_i = L_i + A_{i+1} + U_i$ where L_i is a lower block
 diagonal matrix and U_i is an upper block diagonal matrix,
 (ii) incrementing i , and
 (iii) repeating step (4)(b) for matrix A_{i+1} ;

10 (5) generating a second matrix M_0 that is an approximation to matrix A_0 in accordance with the following steps:

- (a) letting $M_n = A_n - D$ where D is a diagonal matrix defined
 by a specified operation on the matrix given by

$$\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1},$$

- 15 (b) generating, for $i=(n-1)$ to 1,
 $M_i = (L_i + M_{i+1})(I + M_{i+1}^{-1} U_i)$, and
- (c) letting $M_0 = (L_0 M_1^{-1} + I)(M_1 + U_0)$;

(6) generating, for $k=1$ until convergence, the following values:

- 20 (a) $\bar{y} = (L_0 M_1^{-1} + I)^{-1} \bar{r}_{k-1}$,
- (b) $\bar{q} = (M_1 + U_0)^{-1} \bar{y}$,
- (c) $\bar{z}_i = M_{i+1}^{-1} U_i \bar{q}$ (for $i = 1, \dots, n-1$),
- (d) $A_0 M_0^{-1} \bar{r}_{k-1} = \bar{y} + D \bar{q} + L_0 \bar{q} - \sum_{i=1}^{n-1} L_i \bar{z}_i$, and
- (e) \bar{r}_{k+1} by accelerating the value $A_0 M_0^{-1} \bar{r}_{k-1}$;

(7) generating an approximate solution to the system of linear equations representing reservoir conditions using a value of said \bar{r}_{k+1} that converged; and

(8) generating a second signal representing physical characteristics of the reservoir.

9. The method of claim 8, wherein the physical characteristics comprise reservoir pressure at one or more locations, water fraction at one or more locations, oil fraction at one or more locations, and gas fraction at one or more locations.

10. The method of claim 8, wherein matrix A_i can be efficiently factored exactly when it has a bandwidth of less than or equal to approximately 7.

11. The method of claim 8, wherein the specified operation comprises a column sum operation in accordance with the following:

$$COLSUM\left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1}\right).$$

12. The method of claim 8, wherein the specified operation comprises a row sum operation in accordance with the following:

$$ROWSUM\left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1}\right).$$

13. The method of claim 8, wherein said accelerating comprises a generalized minimal residual method.

14. A method for solving a system of linear equations representing reservoir conditions, comprising the steps of:

receiving a first signal representing physical characteristics of a reservoir;

obtaining, from the received signal, a residual vector \vec{r}_0 representing
 5 errors associated with a system of nonlinear equations describing the
 reservoir;

obtaining, from the received signal, a first matrix A_0 representing
 sensitivity of the residual vector \vec{r}_0 to changes in the system of
 10 nonlinear equations describing the reservoir; and

decomposing matrix A_0 in accordance with the following steps:

- (a) letting $i = 0$,
- (b) if matrix A_i can be efficiently factored exactly, letting $n=i$,
 15 else,
 (i) letting $A_i = L_i + A_{i+1} + U_i$ where L_i is a lower block
 diagonal matrix and U_i is an upper block diagonal matrix,
 (ii) incrementing i , and
 (iii) repeating step (4)(b) for matrix A_{i+1} .

20 15. The method of claim 14, further comprising the steps of:

generating a second matrix M_0 that is an approximation to matrix A_0
 in accordance with the following steps:

- (a) letting $M_n = A_n - D$ where D is a diagonal matrix defined by a
 specified operation on the matrix given by

$$\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1},$$

- (b) generating, for $i=(n-1)$ to 1, $M_i = (L_i + M_{i+1})(I + M_{i+1}^{-1}U_i)$,
 and (c) letting $M_0 = (L_0 M_1^{-1} + I)(M_1 + U_0)$.

16. The method of claim 15, further comprising the steps of:

5

generating, for $k=1$ until convergence, the following values:

- (a) $\bar{y} = (L_0 M_1^{-1} + I)^{-1} \bar{r}_{k-1}$,
 (b) $\bar{q} = (M_1 + U_0)^{-1} \bar{y}$,
 (c) $\bar{z}_i = M_{i+1}^{-1} U_i \bar{q}$ (for $i = 1, \dots, n-1$),
 10 (d) $A_0 M_0^{-1} \bar{r}_{k-1} = \bar{y} + D\bar{q} + L_0 \bar{q} - \sum_{i=1}^{n-1} L_i \bar{z}_i$, and
 (e) \bar{r}_{k+1} by accelerating the value $A_0 M_0^{-1} \bar{r}_{k-1}$.

17. The method of claim 14, wherein the physical characteristics
 comprise reservoir pressure at one or more locations, water fraction at
 15 one or more locations, oil fraction at one or more locations, and gas
 fraction at one or more locations.

18. The method of claim 14, wherein matrix A_i can be efficiently
 factored exactly when it has a bandwidth of less than or equal to
 20 approximately 7.

19. The method of claim 14, wherein the specified operation comprises a
 column sum operation in accordance with the following:

25
$$COLSUM \left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1} \right).$$

20. The method of claim 14, wherein the specified operation comprises a row sum operation in accordance with the following:

$$5 \quad \text{ROWSUM} \left(\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1} \right).$$

21. The method of claim 16 wherein said accelerating comprises a generalized minimal residual method.

10 22. A computer program, residing on a computer readable medium, comprising instructions for causing a computer to:

receive a first signal representing physical characteristics of a reservoir;

15 obtain, from the received signal, a residual vector \vec{r}_0 representing errors associated with a system of nonlinear equations describing the reservoir;

obtain, from the received signal, a first matrix A_0 representing sensitivity of the residual vector \vec{r}_0 to changes in the system of

20 nonlinear equations describing the reservoir; and

decompose said matrix A_0 in accordance with the following steps:

(a) let $i = 0$,

(b) if matrix A_i can be efficiently factored exactly, let $n=i$,

25 else,

(i) let $A_i = L_i + A_{i+1} + U_i$ where L_i is a lower block diagonal matrix and U_i is an upper block diagonal matrix,

(ii) increment i , and

(iii) repeat step (4)(b) for matrix A_{i+1} .

23. The computer program of claim 22, further comprising instructions to:

5 generate a second matrix M_0 that is an approximation to matrix A_0 in accordance with the following steps:

(a) letting $M_n = A_n - D$ where D is a diagonal matrix defined by

a specified operation on the matrix given by $\sum_{i=1}^{n-1} L_{i-1} M_i^{-1} U_{i-1}$,

(b) generating, for $i=(n-1)$ to 1, $M_i = (L_i + M_{i+1})(I + M_{i+1}^{-1} U_i)$,

10 and

(c) letting $M_0 = (L_0 M_1^{-1} + I)(M_1 + U_0)$.

24. The computer program of claim 23, further comprising instructions to:

15

generate, for $k=1$ until convergence, the following values:

(a) $\bar{y} = (L_0 M_1^{-1} + I)^{-1} \bar{r}_{k-1}$,

(b) $\bar{q} = (M_1 + U_0)^{-1} \bar{y}$,

20 (c) $\bar{z}_i = M_{i+1}^{-1} U_i \bar{q}$ (for $i = 1, \dots, n-1$),

(d) $A_0 M_0^{-1} \bar{r}_{k-1} = \bar{y} + D \bar{q} + L_0 \bar{q} - \sum_{i=1}^{n-1} L_i \bar{z}_i$, and

(e) \bar{r}_{k+1} by accelerating the value $A_0 M_0^{-1} \bar{r}_{k-1}$.






FIG. 2

FIG.3
(PRIOR ART)

2/10

**FIG.4**




FIG. 5




FIG. 6

4/10

FIG. 6a






FIG. 7





6/10

FIG. 8a
(PRIOR ART)

7/10

FIG. 8b



8/10

FIG. 10




FIG. 11






FIG. 12



10/10

FIG. 13



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/15056

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06F 19/00

US CL : 702/016, 014, 367/072, 073.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 702/016, 014, 367/072, 073.

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
Stic, Society of Petroleum EngineersElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
East, West.
Claim terms, and equations.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,729,451 A (Gibbs et al.) 17 March 1998, (17/03/98), see entire patent.	1-24
A	US 6,061,301 A (Corrigan) 09 May 2000, (09/05/00), see entire patent.	1-24

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	-T-	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A- document defining the general state of the art which is not considered to be of particular relevance	-X-	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E- earlier document published on or after the international filing date	-Y-	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L- document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	-Z-	document member of the same patent family
*O- document referring to an oral disclosure, use, exhibition or other means		
*P- document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

14 JULY 2000

Date of mailing of the international search report

07 SEP 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

VICTOR J. TAYLOR

Telephone No. (703) 305-4470